

18" Indoor/Outdoor Basket Fan for Agricultural Use

Our 18" basket fan is a durable, three-speed, waterproof fan. This fan comes pre-wired with a 115 volt plug and 8' cord for instant operation.



This premium indoor/outdoor waterproof fan is perfect for wash bays where fans may come in contact with rain and humidity. Our UL507 fans can be sprayed down to remove dust and dirt build up, making them an excellent choice for stable applications.

FEATURES

- 18" model available in black or white (black stocked at RAMM)
- High output performance
- 3-speed pull chain
- Attached 8' cord with 3-prong plug pre-wired for 115 volts
- Versatile powder coated mounting bracket allows for easy tilt and swivel of fan to easily change direction and angle of air movement
- · UL507 certified for indoor and outdoor use

- Aluminum blades
- Quiet operation
- Corrosion resistant, powder coated fan guards meet OSHA 1910.212(a)(5) requirements
- Totally enclosed maintenance-free, direct drive high-efficiency motors have completely sealed ball bearings, UL and CUL recognized, and are covered by a **One Year Warranty**
- Rated for use with available misting/fogging products to increase cooling abilities
- GFCI (Ground Fault Circuit Interrupter) recommended on all circuits

| Size | HP | Volts | Amps | Hz | Ph | Spd | FPM* | Thrust (lbf) | Thrust Eff. Ratio** | Kw | RPM | Thrust CFM | Thrust CFM/ Watt | Drive | Blade | Cord | Test # |
|-------|-----|-------|------|----|----|-----|-------------------|----------------------|---------------------------|----------------------|-----------------------|-------------------------|------------------------|--------|-------|-------|--------|
| 18 in | 1/5 | 115 | 2.0 | 60 | 1 | 3 | 755 660 435 | 1.73 1.25 0.72 | 10.9 8.9 6.4 | .159 .140 .112 | 1,550 1,339 994 | 2,210 1,870 1,420 | 13.4 | Direct | 3 | 8 ft. | C0838 |

^{*} FPM (Feet Per Minute) - Velocity measured center line at a distance 5 times the prop diameter.

^{**} Thrust Efficiency Ratio is calculated by dividing the Thrust (lbf) by the kW.