



**6 ROBUST SURGE PROTECTION**  
10kV/6kA surge protection standard for all fixture models. Additional surge protection 20kV/10kA available.

**5 ROBUST DESIGN**  
Sleek, low-profile design with low EPA rating. IP67 and IK10 rated design. Withstands 3G vibration load rating. Dark Sky Approved.



**1 PERFORMANCE**  
Up to 172 LPW at 80 CRI for maximum efficacy and fast ROI. Three light distribution types: Type V, Type IV, and Type III.

**2 6x LIFE\***  
The IAHP1 L70 rating at 150,000 hours is over 6x as long as the typical HID fixture alternatives.



**4 EASY ACCESSIBILITY**  
Buckle design allows for easy access to electrical components for maintenance and installation in the field.

**3 MULTIPLE MOUNTING OPTIONS**

- Slipfitter
- Yoke Mount
- Trunnion Mount
- Adjustable Arm
- Universal Pole Mount
- Slide and Lock Mount
- Adjustable Wall Mount

**FACTORY & FIELD INSTALLED OPTIONS**

- 3/5/7 Pin Photocell Options
- Motion Sensors
- IoT and Wireless Controls
- Field Accessories

8 LUMEN PACKAGES AVAILABLE FOR ANY APPLICATION



Motion Sensor



Photocell



Light Shields

Available in lumen packages from 13,000 to 63,000. 120v-277v and 277v-480v

\*LED rated life based on IAHP1D1UNVFD840 L70 @ 25C ambient vs. HID Lamps.



IP66 IP67

